

The SaniServ® model 614 shake freezer provides high profit, consistent quality shakes in a traditional single barrel flavor design! The 614's ease of operation is a favorite among owners and operators. The high production, capacity and recovery time insures the 614 is a perfect piece of equipment for satisfying high customer demand. By adding a drink spinner and syrup rail, the 614 is sure to provide everyone's favorite shake flavor!



### DESIGNED FOR HIGHER VOLUME APPLICATIONS

Five - 16 oz. Shakes per Minute - 20 Quart Capacity

### Use SaniServ<sup>®</sup> Model 614 to Create





#### About the 614

#### **Cooling Options**









Dimensions: Width (17") Depth (25.8") Height (56.8") Weight (338 lbs)

#### **Electrical Requirements:**

208-230/60/1 = 25 Amps 208-230/60/3 = 20 Amps

#### **Serving Estimate:**

Up to 300 Milkshakes / hr

We reserve the right to change specifications and product designs without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions, or replacements for previously purchased equipment.







## **NEW SCROLL COMPRESSOR**

Provides the SaniServ® model 614 with quieter operation. It is 20% more efficient. Increased durability, with 50% longer service life.

## **SPACE SAVING** - Small Footprint Design

SaniServ® model 614 provides a high volume milkshake in the traditional floor model design.

## **EASY CLEANING AND OPERATION** - Fewer Parts = Simplified Cleaning

SaniServ® equipment is designed and built with the fewest parts to be disassembled, cleaned and sanitized than any other machine in the industry. The state of the art solid-state AccuFreeze® control insures product consistency, worryfree operation and customer satisfaction.

## HIGH RETURN ON INVESTMENT - Increased Profits


SaniServ® machines combine efficiency with consistent product quality and fast, quiet operation while insuring customer satisfaction with high profit ice cream or yogurt products.

## **QUALITY DESIGN** - Durability

SaniServ® machines are built to achieve long and dependable life through simplicity of design. Every machine is shipped standard with a stainless steel exterior, durable steel interior frame construction, heavy-duty components and consistency systems.



Minimum Wall Clearance Both Sides and Back 6 inches (152 mm)



11.8° 300 mm	
30.3° 770 mm	
6.8	18.8° 478 mm 22.0° 559 mm

ELECTRICAL			WIDTH	HEIGHT	DEPTH	WEIGHT	VOLUME		
VOLTS	Hz	Ph.	Amps	INCHES (MM)	INCHES (MM)	INCHES (MM)	LBS. (Kg)	CU FT. (cu. m.)	
208-230	60	1	25	17 (432)	17 (422) 56 0 (1	56.0 (1442) 25.0 (656)	25.0 (656)	220 (4.52)	
208-230	60	3	20		56.8 (1443)	25.8 (656)	338 (153)		
	Shipping Specifications		24.5 (622)	58.1 (1476)	40.5 (1029)	385 (175)	32.4 (.92)		

### **SPECIFICATIONS**

#### **Cooling System:**

Air or Water

#### Dasher and Compressor Motors:

1/4 HP Dasher 2 HP Scroll Compressor

#### **Refrigerator Type:**

R404A

#### Listings:

UL, cUL, NSF

### **FEATURES**

# Evaporator and Mix Reservoir Capacity:

20 Quarts (18.9 liters)

#### Dasher:

Heavy-Duty Stainless Steel with low friction scraper blades.

#### Controls:

AccuFreeze<sup>®</sup> solid-state control for accurate product consistency.

Solid State Audio/Visual Mix Out System with Compressor Lockout

### WARRANTY

Parts 1 year Compressor 5 years Evaporator 5 years

#### Options:

Drink Spinner
Tune Up Kit
Syrup Rail
Water Cooled - 3/4" Garden
Hose Fitting
Wash Out Kit - 3/8" Flare Fitting
Export Voltages